

The Itron logo is located in the top left corner, consisting of the word "Itron" in white lowercase letters on a red rectangular background. The letter "i" has a yellow lightning bolt symbol above it.

Itron


THE CORE OF OUR WATER MANAGEMENT PLATFORM

Intelis




WATER MANAGEMENT PLATFORM

WATER MANAGEMENT CYCLE



1/ EXTENDING WHAT WE MEASURE




1/ EXTENDING WHAT YOU MEASURE



ULTRASONIC MEASURING TECHNOLOGY

PRINCIPLE OF ULTRASONIC MEASUREMENT



Flow Rate:

$$\Rightarrow Q = S.v = 2SL \frac{T2 - T1}{Transit^2}$$

- » Transit time principle:
 - The flow meter operates by alternately transmitting and receiving a wave of sound energy and measures the transit time that it takes for sound to travel between the two transducers.
 - The time is directly related to the velocity of the liquid in the pipe.
- » Flowmeter accuracy is linked to the precision of the measure.
- » X61 precision is 20ps (20 X faster than Intel core micro processor 2,5MHz).

ULTRASONIC TECHNOLOGY KEY BENEFITS



When technology adapts to ALL network conditions

» Different consumption patterns

- Wide dynamic range
- Same accuracy in whole dynamic range
- Not affected by high flow rates and pressure peaks



» Different water temperature

- Measures the temperature
- Same accuracy for different water temperatures from 1°C to 70°C
- Compatible with water up to 90°C



» Water quality

- Not affected or damaged by particles in loaded water



» Intermittent Water supply (Air)

- Air does not affect/damage the meter
- Air is not counted and detected by the meter → alarm



ULTRASONIC TECHNOLOGY KEY BENEFITS



» Accuracy, reliability and long life time

- Linear metrology on complete dynamic range
- Very low starting flow
- Backflow accuracy
- 15 years battery life time (20 years with 2 cells)
- Does not age → long lasting efficiency
- Consumption volume has no impact on metrology

» Installations

- All positions
- No disturbances U0/D0
- Not influenced by electromagnetic fields (pumps, magnets)
- Low head loss
- Resistant to peak flow

» Self diagnostic

- Ensure metrological performances & coherency of the information
- Why ? Due to variable environmental conditions


PERFORMANCE SUMMARY




Characteristics

Permanent flow rate (Q ₃)	1,6 m ³ /h	2,5 m ³ /h	4,0 m ³ /h
Nominal size DN	15	15/20	20
Dynamic range (R)	160 - 200 - 250	160-200-250-315 - 400	160 -200-250-315-400-630
Overload Flow rate (Q ₄)	2,0 m ³ /h	3,125 m ³ /h	5,0 m ³ /h
Minimum Flow rate (Q ₁)	6,4 l/h		
Starting flow	1,5 l/h		
Meter Temperature class	T70 (1°C – 70°C)		
MPA	16 Bars		
Maximum pressure loss at Q ₃	0,40 Bar	0,25 Bar	0,63 Bar
Flow profile sensitivity class	Class U0 D0		
Accuracy class	2		

1/ EXTENDING WHAT YOU MEASURE



ENHANCED FUNCTIONALITIES



Peak flow



Leakage



Event log



Time synchronization



Volume below threshold



Minimum Flow



Time of use



Backflow



Reversed meter



Meter stopped



Custom Billing period




Logging intervals

- Monitor and alerts
- 100% data secured
- Cyble Inside





Flow repartition



Logging intervals


Functionalities from WaterMind

- Real flow rate analysis
- Water balance monitoring
- Consumption pattern analysis







Air in pipe



Broken pipe



Alarm water temperature



Peak temperature



Battery alarm



Alarm reconfiguration




Fraud


New functions



1/ EXTENDING WHAT YOU MEASURE




1/ EXTENDING WHAT YOU MEASURE




- » Flow measuring
 - Instantaneous flow is measured (flow rate is not calculated versus a consumption over a period)
 - Flow rate is measured in both direction
 - Peak & low flow are detected → alarms

- » Permanent monitoring solution
 - 100% time monitoring on complete lifetime
 - Not only measure when there is water consumption, flow rate is continuously monitored and detects when there is no water.

1/ EXTENDING WHAT YOU MEASURE



EVOLUTIVE PLATFORM



» Temperature monitoring

- Control water temperature for quality
- Prevent sanitary risk for inhabitants
- Prevent water frozen
- Record operating conditions over the water network





» Air detection

- When air is detected, Meter Stop counting and alarm is activate
- No air is counted on the meter Index. Meter records the time spent under Air Operation.
- Detect zones of the network with non permanent supply




EVOLUTIVE PLATFORM


- Pressure (optional feature)
 - Network optimization
 - Detection of weak zones
 - Reduction of leakages and weak zones
 - Energy saving
- Leak sensor (optional feature)
 - Network optimization
 - Detection of weak zones
 - Reduction of leakages and weak zones



2/ SECURING WHAT YOU COLLECT






2/ SECURING WHAT YOU COLLECT





» Global solution

- Radio embedded
- Itron RF 433 MHz (radian)
- AnyQuest & EverBlu enhanced
- Architecture ready for other radio standard (OMS/DSMR/Zigbee).





Hand Held terminal for mobile network

2/ SECURING WHAT YOU COLLECT




2/ SECURING WHAT YOU COLLECT





3/ CREATING ACTIONABLE DATA

Analyze



AMI DATA FLOW



Data repository offers storage and advanced analytics



Note: Software can be installed locally or hosted by Itron Private Cloud Services.

DISTRICT METERING

Comparative analysis to detect Non-Revenue Water





» Detect Non-Revenue Water (“NRW”) system-wide or zone-by-zone by comparing the outflow of a master (or “district”) meter to the aggregated consumption of the corresponding district on a time-synchronized interval-by-interval basis as shown during POC

» Includes enhanced capabilities to import groups directly from GIS as well as create groups based on advanced searches

FLOW ANALYSIS & METER RIGHT-SIZING



Actionable data for meter shop and distribution



» Also have the ability to compare “high” side to “low” side of a compound meter

CUSTOMER WEB PORTAL

Itron's end-user web portal displays and compares consumption data



» Allow end-use customers to log-on and view their own reads

- Bar or Line Chart Radio Button
- Optional Weather Trend Line

» Ability for customer to view their consumption against pre-selected “averages” groups defined by utility

» Ability for customer to set target consumption limits, and to be notified via email/text when limit is within xx% (10% default) of being exceeded, and when it has been exceeded

THANK YOU



www.itron.com