





AFC Multi-Purpose Coating

Product	FORTRESS AFC Multi-Purpose Coating	
Introduction		
Recommendation	AFC is a multi-purpose coating designed to protect a variety of surfaces including asphalt, PVC, TPO, rubber, concrete, foam, wood and metal. AFC is also suitable for underwater location. It's also a Non-Toxic and Low VOC Paint.	
Features	<ul style="list-style-type: none"> • Adheres even to damp surfaces without priming. • Withstands ponding water. • Can be installed in freezing conditions and retains flexibility in sub zero conditions • Can be applied under direct sunlight • Withstands attacks from most chemicals, traffic, and severe environments. • Class "A" fire rated. • Adhesion Strength 203 lbs/sq.in. • VOC<10g/L according to China National Standard. • Comply with ANSI/AWWA C21. • Com I with BS6920 and suitable for drinking water uses. 	
Specifications		
Colour	Standard color white & grey; Customized colors and specs available.	
Finish	Gloss	
Theoretical Coverage	3 sq.m. / Kg / Coat @ 0.4mm film thickness	
Drying Time (25° C and 50% RH)	<ul style="list-style-type: none"> • Set to touch - 3 hours • Tack free - 5 hours • Roughly dry - 16 hours <p>* Based on theoretical consumption; factors such as colour, application, surrounding environment and substrate conditions will affect the actual consumption.</p>	
Packaging		
	(Part A) 3.4kg/bucket ; (Part B) 1.0kg/bucket	
		
	AFC -Part A	AFC -Part B



AFC Multi-Purpose Coating

Combination	
Surface Coats	FORTRESS AFC Multi-purpose Coating for 2 coats.
Direction for Use	
Tools	Brush roller or airless spray
Mixing Ratio	<ul style="list-style-type: none"> • By volume - Part A: Part B =2 : 1 • By weight - Part A: Part B =3.4 : 1
Application	Wash area with high pressure washer, simple mix 2 parts of A to 1 part of B by volume, mix thoroughly with drill mixer and apply directly to wet surface by brush, roller or airless sprayer.
Cautions	<p>[Eye] Hold eyelids apart and flush thoroughly with water for 15 minutes.</p> <p>[Skin] Remove contaminated clothing. Wash skin thoroughly for 20 minutes with soap and cold water until product cures.</p> <p>[Inhalation] Remove person to fresh air.</p> <p>[Ingestion] Do not induce vomiting. In all cases, contact a physician immediately if symptoms persist.</p>
Shelf Life	
	12 months. Please store in a cool and dry place.
Main Usage	
	<p>Water tank repair and protection for portable water.</p> <p>On any Water Pipe/Fitting and Valve</p> <p>On any material near sea water, e.g. Public pier steps, wall etc.</p> <p>On Hand Railing, road kerb, Fire Hydrant.</p> <p>On Boat, living cube, any area above sea water level.</p>
Manufacturer and Origin	
Manufacturer	Guangdong Fortress Chemical Co., Ltd
Origin	Economic Development Zone Xinhui District, Jiangmen City, Guangdong China
Limitation Liability	
	<p>To the best of our knowledge, the technical data contained herein are true and accurate at the date of issuance but are subject to change without prior notice. We guarantee our product to conform to the specification contained herein.</p> <p>Date of issuance: 17th September, 2017</p>



WELL GROUP (HK) LIMITED

Mobile: 9482 3284
Email: wilson.fung@wellgroupkh.com

Fortress Chemical Co. Ltd.

www.fortress.com.cn