

ATS 250

Electrofusion Welder

- Electrofusion processors for plastic pipe welding world-wide
- Welds constant voltage electrofusion fittings commonly 39.5/40V
- Suitable for low, medium and high pressure PE or PP pipe work systems from 16mm to 400mm diameter (1/2" to 8")
- Welding output is a controlled voltage between 8V and 48V
- Suitable for the rental market and construction sites
- x2 models - Manual or Extra with Barcode
- Welds fittings in Manual mode and Barcode automatic mode
- Data log memory of more than 2000 welds
- Download data log using USB memory
- Hanger to store Input and Output cables
- Optional Barcode Scanner & Bag
- Compact design - easy to transport
- Easy to use operator interface as well as a vibrant, easy to read screen
- Reasonably priced reliability - very popular for those looking for value for money and weight saving
- CE approved

Specification details - ATS250

Operating Modes	Manual, Barcode
Welding Voltage	39.5V (8 to 48V)
Welding Current	1-60A
Welding Time	1-3000 seconds
Supply Voltage	115V±15% 110V (40-60Hz) 230V±15% 230V (40-60Hz)
Supply Current	1-28A (115V) 1-14A (230V)
Supply Power	3500 W
Weight	20 kg
Size	22 x 26 x 45 cm
Operating Temp.	-15C to +50C

